

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A41D 31/00, 13/00	A1	(11) International Publication Number: WO 00/69293 (43) International Publication Date: 23 November 2000 (23.11.00)
<p>(21) International Application Number: PCT/GB00/01832</p> <p>(22) International Filing Date: 12 May 2000 (12.05.00)</p> <p>(30) Priority Data: 9911056.1 12 May 1999 (12.05.99) GB</p> <p>(71) Applicant: PLANT, Daniel, James [GB/GB]; Llanwinney Farm, Llangovan, Nr.Monmouth NP5 4BU (GB).</p> <p>(74) Agent: WOODWARD, John, Calvin; Venner, Shipley & Co., 20 Little Britain, London EC1A 7DH (GB).</p>	<p>(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>	
<p>(54) Title: ENERGY ABSORBING PROTECTIVE MEMBER</p> <p>(57) Abstract</p> <p>A protection member primarily for use as an energy absorbing pad for incorporation into garments to protect the wearer against accidental impacts. The member comprises a putty-like energy absorbing material (2) encapsulated in a flexible envelope (3, 4). The energy absorbing material is normally soft and flexible but changes to become temporarily rigid when an impact force is applied thereto, thereby absorbing the impact energy, the material returning to its normal flexible condition after the impact. The energy absorbing member preferably comprises a series of connected corrugations (8) to increase its energy absorbing properties.</p> <div data-bbox="646 1157 1356 1858"> </div>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

WO 00/69293

PCT/GB00/01832

- 1 -

Energy Absorbing Protective Member

This invention relates to a new energy absorbing member which is particularly applicable for protection and is especially suitable for
5 incorporation into garments or apparel worn by people who need their body parts protected against impact. The protective member can also be mounted on an object such as a door frame or wall edge which a person might accidentally come into contact with.

10 The protective member of the invention is particularly applicable for use in the medical field, by sportsmen, motor cyclists, urban street wear (cycling/rollerblading), work wear, body armour, riot police gear, oil riggers gear or film crews etc. as well as many other applications such as in crash barriers or as an energy absorbing wall or floor covering.

15 One established way of absorbing and/or spreading impact energy is to make a pad out of an energy absorbing material. Such pads are generally made of foam and are either worn by the person who needs protection or attached to the part of the fixture likely to be impacted. Static pads
20 can be flexible or rigid as they do not need to bend in use. In some applications, a rigid pad is worn by the wearer. For instance, as a shin pad in the case of a rugby or soccer player or a forearm pad in the case of a cricketer as neither of these limb parts need to bend or articulate in use. However, where a joint needs to be protected, a high degree of
25 flexibility is required so the protective pads need to be made of a flexible material to give the wearer the required level of mobility to make the pad comfortable to wear.

WO 00/69293

PCT/GB00/01832

- 2 -

Body impact protection currently available is limited because it is either based on a rigid exterior shell (for example as used as roller blade pads) or upon some form of foam laminate (as used in ski pant inserts). However, foam laminates provide poor levels of protection and rigid
5 shells are uncomfortable to wear.

It is an object of the present invention therefore to provide a protective member which absorbs and spreads impact energy and is soft and flexible yet has high energy absorbing properties. It is a further object
10 of the invention to provide an energy absorbing member which can be permanently attached and tailored into a garment or part thereof.

According to the invention there is provided a protective member comprising an energy absorbing material in an envelope which contains
15 said material in a controlled space, the energy absorbing material remaining malleable until it is subjected to an impact when its characteristics change rendering it temporarily rigid, the material returning to its normal malleable condition after said impact.

20 Preferably the energy absorbing material is encapsulated in the envelope and absorbs the impact force and spreads the load thereof during the duration of the impact. Preferably the energy absorbing material is a strain rate sensitive material such as a dilatant compound whose mechanical characteristics change on impact.

25

The preferred material is a Dimethyl siloxane hydroterminated polymer such as the material sold by DOW CORNING under their Catalogue or Trade number 3179.

WO 00/69293

PCT/GB00/01832

- 3 -

The encapsulating envelope can be made of foam, fabric, plastic, rubber or metal or a combination of these materials, to contain the energy absorbing material and prevent egress thereof from the envelope. The
5 envelope is however preferably made from an elastomer which conveniently is thermo plastic. A thermoplastic polyester elastomer preferably having a crystalline PBT hard segment with an amorphous glycol soft segment has been found to be particularly suitable. The preferred material is the thermo plastic elastomer sold by Dupont under
10 their Trade Mark HYTREL.

The encapsulating envelope can be substantially planar but is preferably corrugated along its length. The angle of the sides of each corrugation is not critical but 54° has been found to give excellent energy absorbing
15 results.

The encapsulating envelope has an outer and inner surface and, a flexible foam layer can be attached to said inner surface. For some uses, the foam layer may be attached to only one surface or both the inner and
20 outer surfaces.

In another embodiment, the protective member is a channel shaped segment which is arcuate along its length. A plurality of these segments can be joined together to form a sheet of protective material with the
25 longitudinal axis of one segment at 90° to an adjacent segment. In order to form the sheet, the corners of each segment are connected to the corners of a contiguous segment.

WO 00/69293

PCT/GB00/01832

- 4 -

Several embodiments of the invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

- Figure 1 is a perspective view of a protective member of the invention;
5 Figure 2 is a cross section of the protective member shown in Figure 1;
Figure 3 is a perspective view of a corrugated protective member;
Figure 4 is a cross section through the corrugated protective member of Figure 3;
Figure 5 is an enlarged view of the portion of the protective member
10 circled in Figure 4;
Figure 6 is a view of a protective segment of the invention;
Figure 7 is a view of a sheet of material made up from a plurality of interconnected protective segments shown in Figure 6;
Figure 8 is a perspective view of a person wearing a garment
15 incorporating protective members of the invention;
Figure 9 is a view of another form of protective member of the invention for use as an elbow protector;
Figure 10 is a cross sectional view of another form of protective member; and
20 Figure 11 is a view of the protective member of Figures 8 and 9 in position on a wearer's shin.

Figures 1 and 2 show a protective member 1 of the invention which comprises a quantity of energy absorbing material 2 encapsulated in an
25 envelope comprising an upper layer 3 and a lower layer 4 connected together at their periphery 5 to provide a sealed enclosure for the material 2. The envelope can however be blow moulded from a single piece of material.

WO 00/69293

PCT/GB00/01832

- 5 -

The energy absorbing material 2 can be a strain rate sensitive polymer, a non-Newtonian fluid or a dilatant compound which is normally malleable under low strain rates and behaves in a manner similar to a putty like substance. However, when an impact is applied to the material 2, it momentarily changes from being malleable and instantaneously becomes rigid thereby absorbing and spreading the impact energy. The preferred material is a dimethyl siloxane hydroterminated polymer such as the material manufactured by DOW CORNING and sold under their catalogue or trade No. 3179.

The encapsulating layers 3 and 4 are preferably made of a thermo plastic elastomer material manufactured by Du Pont and sold under their trade mark HY-TREL. This material is strong enough to withstand the impact energy without the material tearing or fracturing but at the same time allows the impact energy to be transferred through the material layer 3,4 to be absorbed by the putty-like energy absorbing material 2.

This unique multi-layer energy absorbing member can flex with movement of the body when protection is not needed and thus is very comfortable to wear. When impacted however, the strain rate sensitive polymer in the energy absorbing member reacts instantaneously to form a semi-rigid structure that absorbs and dissipates the blow giving maximum protection. Independent tests have confirmed that the energy absorbing member of the invention is substantially more effective than conventional foam and/or plastic systems.

WO 00/69293

PCT/GB00/01832

- 6 -


The Active Protection System (APS) of the invention has been impact tested and the results compared with identical impact tests carried out on a known impact protection member sold to motorcyclists under the trade mark "Dianese". In order to record the magnitude of pressure and force distribution on impact, a special film is used which changes colour in accordance with the level of impact pressure that it receives.

In order to carry out the test, a piece of Dianese and APS of the invention were impacted in a comparative test and the four photographs hereafter record the impact.

DIANESE (prior art)

APS (invention)

15




Dianese Outside




APS Outside

20



Dianese Inside



APS Inside

25

(less black shows lower pressure, i.e. better protection).

WO 00/69293

PCT/GB00/01832

- 7 -

It can be seen from the photographs that the APS energy absorbing member of the invention performed significantly better than the known "Dianese" pad because only very light grey areas are visible on the inside surface of APS member whereas substantial black areas are visible on the inside surface of the Dianese member. This clearly demonstrates that the APS member of the invention provides a much higher level of protection as comparatively very little force has passed through to its inside surface.

10

Figures 3-5 show an alternative form of energy absorbing member in accordance with the present invention which has a corrugated configuration with a plurality of convolutions to increase its energy absorbing properties. The energy absorbing member comprises the energy absorbing material 2 encapsulated between sheets of HY-TREL 3 and 4 which are sealed at 5 around their periphery to contain the material 2 within the envelope (see Figure 4). The construction of the corrugated energy absorbing member shown in Figures 3-5 is the same as that shown in Figures 1 and 2 except that the member has the series of corrugations 8 along its length. To increase its energy absorbing properties and also for increased comfort, a layer of foam 9 can be attached to inner layer 7 of membrane 4. The envelope has to be of a thickness which is sufficient to enable it to return to its original configuration after impact. 0.5-1.5mm has been found to be particularly satisfactory.

25

Referring now to Figure 5, when an impact load I is applied to the energy absorbing member 1 in the direction of the arrow, the load I will

WO 00/69293

PCT/GB00/01832

- 8 -

be dissipated by the apexes 8A of the convolutions down either side thereof which creates shear forces as the material hardens thereby absorbing the impact load. Preferably the apices 8A are curved rather than pointed as this further assists in dissipating the impact load I down
5 either side of each of the corrugations 8.

It should be noted that the foam backing 9 is preferred rather than essential and is usually provided on the inner surface of the energy absorbing member for increased comfort for the wearer.

10

Figure 6 shows an alternative form of energy absorbing member 1 in accordance with the present invention which is particularly suitable for use in making up a sheet of material as shown in Figure 7. Each energy absorbing member 1 comprises an outer membrane 3 and an inner
15 membrane 4 between which the putty-like energy absorbing material 2 is encapsulated. The energy absorbing member 1 can be channel or arch shaped and conveniently but not essentially has connecting means in the form of a foot or pad 10 at each corner thereof having a hole 11 therein. It can however be cone shaped or of any energy absorbing profile.

20

As can be seen more clearly in Figure 7, the plurality of the channel shaped energy absorbing members 1 can be connected together for instance by means of their feet 10 to form a sheet of material which is flexible and bendable in several planes. Each energy absorbing member
25 1 of the sheet works in exactly the same way as the energy absorbing member just described in that when an impact load is applied to the sheet of material, the normally malleable energy absorbing material 2 within each member 1 temporarily becomes rigid thereby absorbing the

WO 00/69293

PCT/GB00/01832

- 9 -

load, the material 2 returning to its normal malleable state shortly after the impact energy has been absorbed.

The configuration of the sheet illustrated in Figure 7 is only one example
5 of the way in which a sheet of material can be formed using individual energy absorbing members 1 connected together with their longitudinal axis normal to each other. Other configurations are however possible.

A particularly useful application of energy absorbing members of the
10 present invention is shown in Figure 8 where an energy absorbing elbow pad 16 and a shoulder pad 17 is incorporated into garment 15. Similar pads can be incorporated into the knee, shin or thigh area of a pair of trousers (not shown).

15 Figure 9 shows a design of elbow pad in accordance with the present invention which comprises an elongate main body section 20 having optional out-riggers 21,22 attached to the main body section by means of spars 23. The main body section 20 has a dome shaped section 24 to receive the wearer's elbow joint. The energy absorbing member
20 illustrated in Figure 9 is of the same construction as the embodiments already described in that it comprises an energy absorbing putty-like material 2 encapsulated between inner and outer layers 3 and 4 made of HYTREL. The main body section 20 and the out-riggers 21 are corrugated as illustrated and are therefore similar in construction to the
25 protective member shown in Figures 4-7.

In use, the wearer would place the main body section 20 inside the garment sleeve with their elbow joint located within the dome shaped

WO 00/69293

PCT/GB00/01832

- 10 -

section 24. The elongate body section 20 would extend down the
wearer's arm generally coaxial therewith and the out riggers 21 and 22
would be folded around the arm on either side thereof. Thus, the elbow
region would be protected against direct impacts on the elbow joint itself
5 and also the portions of the arm on either side of the elbow joint would
be protected. The protective member shown in Figure 9 can either be
inserted within the wearer's sleeve for instance into a stretch pocket or
alternatively can be attached to the fabric from which the garment is
made as an integral part thereof e.g. by stitching or thermal attachment.

10

Whilst the embodiment shown in Figure 9 is an elbow pad, it will be
appreciated that the design thereof could be changed while still operating
in the same way to protect other body parts such as shoulders, knees or
hips.

15

Figures 10 and 11, show a further embodiment of energy absorbing
member 1 of the present invention which comprises a textile layer or
tube 12 to which an energy absorbing pad of the invention is attached to
protect, for example, a knee, elbow or hip joint. The energy absorbing
20 member 1 comprises an outer layer 3 and an inner layer 4 preferably
made of a material such as HYTREL between which is encapsulated the
putty-like malleable material 2. The edges of the layers 3 and 4 are
preferably connected together at 5 to seal the putty-like material within
the envelope 3,4. The layers 3 and 4 can however be made of a textile
25 material whose surfaces are coated, preferably with a water proofing
material such as polyurethane or any other membrane which will
encapsulate and contain the malleable material 2.

WO 00/69293

PCT/GB00/01832

- 11 -

To assist its energy absorbing properties, an annular foam ring 13 can be attached to inner surface 7 of the membrane 4. A spacer 14 made from a textile material is preferably provided within the annular foam ring 13 to ensure that the putty layer 2 does not come into contact with the
5 users limb to be protected.

As can be seen more clearly in Figure 11, when the impact load I is applied to the energy absorbing member 1 fitted to a limb 12 of a wearer, the energy impact is initially dissipated laterally in the directions
10 of arrows T thereby deflecting the impact load I away from the wearer's shin bone 12A. The initial impact is absorbed by the putty-like material 2 which changes from its malleable state to its rigid state but the load is then transferred laterally to the outer edges of the member 1 where it is absorbed as load E in the foam ring 3 and the soft skin or muscle of the
15 wearer's limb 12. It will be appreciated that the energy absorbing member just described and illustrated moves the impact force I away from the bone 12A and into layer 3 and the fatty tissue in the leg. The energy absorbing member 1 can be shaped to include the convoluted sections 8 shown in Figures 3-5 or 9.

20

The Active Protection System (APS) of the invention protects the human body from abrasions and impacts. This flexible system can be incorporated directly into a garment. The APS is malleable under normal conditions and will easily conform to the movements of the body
25 and is therefore non-restrictive. Upon impact the APS becomes momentarily rigid, spreading and absorbing the impact force before returning to its normal flexible, comfortable state.

WO 00/69293

PCT/GB00/01832

- 12 -

The APS is made from two materials combined in layers. The heart of the system is the active strain rate sensitive polymer material 2 which reacts to impact, and is encapsulated in the flexible outer sheath 3,4. The system has been designed to work synergistically producing a significant increase in impact performance, over and above that of either material in isolation.

WO 00/69293

PCT/GB00/01832

- 13 -

Claims

1. A protective member comprising an energy absorbing material in an envelope which contains said material in a controlled space, the
5 material remaining soft and flexible until it is subjected to an impact when its characteristics change rendering it temporarily rigid, the material returning to its normal flexible condition after said impact.
2. A protective member as claimed in claim 1 wherein the energy
10 absorbing material is encapsulated in the envelope.
3. A protective member as claimed in claim 1 or claim 2 wherein the mechanical characteristics of the material change on impact.
- 15 4. A protective member as claimed in any preceding claim wherein the energy absorbing material will absorb energy and spread the load thereof for the duration of the impact.
5. A protective member as claimed in any preceding claim wherein
20 the energy absorbing material is a strain rate sensitive material.
6. A protective member as claimed in any preceding claim wherein the energy absorbing material is a dilatant compound.
- 25 7. A protective member as claimed in any preceding claim wherein the energy absorbing material is a dimethyl siloxane hydroterminated polymer.

WO 00/69293

PCT/GB00/01832

- 14 -

8. A protective member as claimed in any preceding claim wherein the energy absorbing material is made by DOW CORNING and sold under catalogue number 3179.
- 5 9. A protective member as claimed in any preceding claim wherein the encapsulating envelope is substantially planar.
- 10 10. A protective member as claimed in any of claims 1-8 wherein the encapsulating envelope is corrugated along its length and comprises a plurality of wave shaped convolutions.
11. A protective member as claimed in claim 10 wherein the angle of the sides of each convolution is 54° .
- 15 12. A protective member as claimed in any preceding claim wherein the encapsulating envelope has an inner face to which a flexible foam layer is attached.
- 20 13. A protective member as claimed in any of claims 1-8 wherein the protective envelope is channel shaped and arcuate along its length to provide a protective segment.
- 25 14. A protective member as claimed in any preceding claim wherein the encapsulating envelope is made of foam, fabric, plastic, rubber or metal or a combination of these materials, to contain the energy absorbing material and prevent egress thereof from the envelope.

WO 00/69293

PCT/GB00/01832

- 15 -

15. A protective member as claimed in any preceding claim wherein the envelope is made of an elastomer.
16. A protective member as claimed in claim 10 wherein the elastomer
5 is a thermoplastic elastomer.
17. A protective member as claimed in claim 16 wherein the elastomer is a polyester elastomer.
- 10 18. A protective member as claimed in claim 17 wherein the elastomer has a crystalline PBT hard segment with an amorphous glycol soft segment.
19. A protective member as claimed in any of claims 14-18 wherein
15 the envelope is made of the thermoplastic elastomer sold by DuPont under the Trade Mark HYTREL.
20. A sheet of protective material made from a plurality of protective segments as claimed in claim 13 wherein a plurality of said segments are
20 connected together to form the sheet.
21. A sheet of protective material as claimed in claim 20 wherein each segment has a longitudinal axis and one segment is connected to an adjacent segment with its longitudinal axis at 90° thereto.
- 25 22. A sheet of protective material as claimed in claim 20 or claim 21 wherein each segment has means thereon to enable it to be connected to

WO 00/69293

PCT/GB00/01832

- 16 -

an adjacent segment, the edges of contiguous segments being joined together to form the sheet.

23. A sheet of protective member as claimed in claim 22 wherein the
5 connecting means are feet.

24. A length of textile material with a protective member or protective
sheet as claimed in any of claims 1-19 or claims 20-23 permanently
attached thereto.

10

25. A garment or part thereof made from a textile material as claimed
in claim 24.

26. A protective member substantially as herein described with
15 reference to Figures 1-6 or Figures 8-11.

27. A sheet of protective material substantially as herein described
with reference to Figure 7 of the accompanying drawings.

WO 00/69293

PCT/GB00/01832

1/5




FIG. 1




FIG. 2




FIG. 3

WO 00/69293

PCT/GB00/01832

2 / 5




FIG. 4




FIG. 5






FIG. 6

WO 00/69293

PCT/GB00/01832



3/5



WO 00/69293

PCT/GB00/01832

4 / 5



WO 00/69293

PCT/GB00/01832

5 / 5




FIG. 11

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 00/01832

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A41D31/00 A41D13/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A41D A47C A61F A61G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)
EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 599 290 A (HAYES WILSON C ET AL) 4 February 1997 (1997-02-04) column 4, line 49 - line 51 column 6, line 48 - line 49 column 7, line 56 - line 60 column 10, line 60 - line 63; figures 1,3,10 ---	1-6,9, 14-17, 24-27
A	US 3 663 973 A (SPENCE WAYMAN R) 23 May 1972 (1972-05-23) claims 1,3,4,7,9; figures 2,7 ---	1,2,7,9, 14,24,26
A	US 5 138 722 A (URELLA RICHARD M ET AL) 18 August 1992 (1992-08-18) column 2, line 62 -column 3, line 10; figures 2-6 --- -/--	1-8,14, 26

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

9 August 2000

Date of mailing of the international search report

17/08/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Monné, E

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 00/01832

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 507 866 A (DREW TERRENCE M ET AL) 16 April 1996 (1996-04-16) column 2, line 30 - line 39 column 3, line 15 column 8, line 14 - line 20 column 19, line 19 - line 20; claim 1; figures 1,2 ---	1,2,7,8, 14,26,27
A	US 5 090 053 A (HAYES HARRY D) 25 February 1992 (1992-02-25) column 4, line 20 - line 25 column 4, line 39 - line 44; claim 3; figure 5 -----	1,2,7,8, 15,25,26

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 00/01832

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5599290 A	04-02-1997	AT 162049 T	15-01-1998
		AU 686065 B	29-01-1998
		AU 1666697 A	12-06-1997
		AU 679197 B	26-06-1997
		AU 5671194 A	22-06-1994
		CA 2147878 A	09-06-1994
		DE 69316390 D	19-02-1998
		DE 69316390 T	10-06-1998
		DK 669811 T	25-05-1998
		EP 0669811 A	06-09-1995
		EP 0797933 A	01-10-1997
		ES 2112515 T	01-04-1998
		JP 8503526 T	16-04-1996
		WO 9412066 A	09-06-1994
		US 5545128 A	13-08-1996
US 3663973 A	23-05-1972	NONE	
US 5138722 A	18-08-1992	NONE	
US 5507866 A	16-04-1996	US 5407481 A	18-04-1995
		US 5204154 A	20-04-1993
		US 5100712 A	31-03-1992
		US 5093138 A	03-03-1992
		AU 3442193 A	05-10-1993
		CA 2131457 A	03-09-1993
		WO 9317859 A	16-09-1993
		AU 6513690 A	18-04-1991
		CA 2066685 A	22-03-1991
		EP 0493505 A	08-07-1992
		WO 9104290 A	04-04-1991
US 5090053 A	25-02-1992	NONE	